



# XM Monitoring Modules Specifications

## Catalog Numbers 1440 series

The XM series of intelligent I/O modules process, in real-time, the critical parameters used to assess the current health and predict the future health of industrial machinery—providing machinery protection and reducing downtime. Use the XM modules in a standalone system, or integrate them with existing automation and control systems.

Type	Module	Cat. No.	Page
Measurement modules	XM DYN Dynamic Measurement Module	1440-DYN02-01RJ	3
	XM-124 Standard Dynamic Measurement Module	1440-SDM02-01RA	6
	XM-160 Direct (overall) Vibration Module (1440-VDRS06-00RH)	1440-VDRS06-00RH	10
	XM-161 Direct (overall) Vibration Module with 4...20 mA Out (1440-VDRS06-06RH)	1440-VDRS06-06RH	10
	XM-162 Direct (overall) Vibration Module with Proximity Probe Power (1440-VDRP06-00RH)	1440-VDRP06-00RH	10
	XM-220 Dual Speed Module	1440-SPD02-01RB	13
Process modules	XM-320 Position Module	1440-TPS02-01RB	16
	XM-360 Process Module	1440-TPR06-00RE	19
Temperature modules	XM-361 Universal Temperature Module	1440-TUN06-00RE	22
	XM-362 Isolated Thermocouple Temperature Module	1440-TTC06-00RE	22
Relay modules	XM-440 Master Relay Module	1440-RMA00-04RC	25
	XM-441 Expansion Relay Module	1440-REX00-04RD	27
	XM-442 Voted EODS Relay Module	1440-REX03-04RG	29
Accessories	Terminal Bases	1440-TB-A, 1440-TB-B, 1440-TB-C, 1440-TB-D, 1440-TB-E, 1440-TB-G, 1440-TB-H, 1440-TBS-J	31
	Serial Configuration Utility	N/A	32
	Fuse Kit	1440-5AFUSEKIT	33
	Serial Communication Cable	1440-SCDB9FXM2	33
	ControlNet Adapter	1440-ACNR	34

## XM-361 Universal Temperature Module

## XM-362 Isolated Thermocouple Temperature Module

The XM-361 (1440-TUN06-00REA) and XM-362 (1440-TTC06-00REA) modules measure temperature from RTDs and thermocouples. The modules report, and can alarm on, the measured temperature, rate of change for each channel, and difference between adjacent channels.

When only thermocouples are monitored, the XM-362 module is the preferred solution.

Attribute	XM-361 (1440-TUN06-00RE) XM-362 (1440-TTC06-00RE)
<b>Inputs</b>	
Channels	1...6 RTD or thermocouple signals, user configurable XM-361 accepts RTD and isolated thermocouple inputs XM-362 accepts isolated or grounded thermocouple inputs
Supported thermocouple types (XM-361 and XM-362)	<ul style="list-style-type: none"> <li>B 0...1810 °C (32...3290 °F)</li> <li>C 0...1316 °C (32...2400 °F)</li> <li>E 5...284 °C (41...543 °F)</li> <li>J 0...364 °C (32...687 °F)</li> <li>K -40...484 °C (-40...903 °F)</li> <li>N -40...620 °C (-40...1148 °F)</li> <li>R -40...1760 °C (-40...3200 °F)</li> <li>S -40...1760 °C (-40...3200 °F)</li> <li>T -40...379 °C (-40...714 °F)</li> </ul>
Supported RTD types (XM-361 only)	<ul style="list-style-type: none"> <li>100 Ω 2-wire and 3-wire platinum (alpha = 0.00385) -40...660 °C (-40...1220 °F)</li> <li>200 Ω 2-wire and 3-wire platinum (alpha = 0.00385) -40...453 °C (-40...847 °F)</li> <li>100 Ω 2-wire and 3-wire platinum (alpha = 0.003916) -40...660 °C (-40...1220 °F)</li> <li>200 Ω 2-wire and 3-wire platinum (alpha = 0.003916) -40...443 °C (-40...829 °F)</li> <li>250 Ω 2-wire and 3-wire platinum (alpha = 0.00392) -40...389 °C (-40...732 °F)</li> <li>100 Ω 2-wire and 3-wire nickel (alpha = 0.00618) -40...180 °C (-40...356 °F)</li> <li>120 Ω 2-wire and 3-wire nickel (alpha = 0.00672) -40...439 °C (-40...822 °F)</li> <li>10 Ω 2-wire and 3-wire copper (alpha = 0.00427) -40...260 °C (-40...500 °F)</li> </ul>
RTD current source value	1.004 mA ±1%

Attribute	XM-361 (1440-TUN06-00RE) XM-362 (1440-TTC06-00RE)
Common mode input voltage (XM-361 only)	±3V
Input impedance	XM-361: 1 MΩ voltage input XM-362: 10 kΩ voltage input
<b>Outputs</b>	
4...20 mA outputs	Two isolated banks of three outputs (one per channel) 600 Ω max load
Accuracy	±1% of full scale, max ±0.2% of full scale, typical
Isolation	250V
<b>Indicators</b>	
Status indicators	Module - red/green Network - red/green Channel 1 - yellow/red Channel 2 - yellow/red Channel 3 - yellow/red Channel 4 - yellow/red Channel 5 - yellow/red Channel 6 - yellow/red
<b>Communication</b>	
DeviceNet network	Standard DeviceNet protocol for all functions (not power—module power is provided independently) Available EDS file provides support for most DeviceNet compliant systems Communication rate automatically set by bus master to 125, 250, or 500 Kbps Configurable I/O Poll Response message helps optimize space utilization within scanner input tables: Selectable poll response assembly Selectable poll response size (bytes)
Serial	RS-232 via mini-connector or terminal base unit Communication rate fixed at 19.2 Kbps Local configuration via the Serial Configuration utility
<b>Signal Conditioning</b>	
Accuracy	C thermocouples: ±3 °C (±6 °F) or 0.6% of full scale, whichever is greater E, J, K, N, T thermocouples: ±1 °C (±2 °F) or 0.6% of full scale, whichever is greater B, R, S thermocouples: ±4 °C (±7 °F) or 0.6% of full scale, whichever is greater Platinum and nickel RTDs (3-wire only): ±1 °C (±2 °F) or 0.6% of full scale, whichever is greater Copper RTDs (three-wire only): ±7 °C (±13 °F) or 5% of full scale, whichever is greater
Resolution	0.025% of temperature range

<b>Attribute</b>	<b>XM-361 (1440-TUN06-00RE) XM-362 (1440-TTC06-00RE)</b>	<b>Attribute</b>	<b>XM-361 (1440-TUN06-00RE) XM-362 (1440-TTC06-00RE)</b>	
Low pass filter	User configurable for the measurement and rate of change value from each channel	Nonvolatile configuration	A copy of the module configuration is retained in nonvolatile memory from which the configuration is loaded upon powerup. The configuration stored in nonvolatile memory can be deleted only by a module-reset command sent via a serial interface, using the Serial Configuration utility or via a DeviceNet interface from any compliant software application	
Sampling rate	200 Hz	<b>Configuration</b>		
Units	°C, °F	<b>Power</b>		
<b>Measurements</b>				
Measured value	Temperature	Module	24V DC Class 2/SELV	
Rate of change	Per minute Updated once per second	Consumption	400 mA, max for XM-361, 300mA for XM-362	
<b>Delta Time Buffer</b>				
Number of records	2048	Heat production	7.2 W (24.6 BTU/hr), max 4 W (14 BTU/hr), typical	
Delta time interval	1...3600 s	<b>Environmental</b>		
Trigger mode	Relay on an XM-441 expansion relay module is activated, or by a trigger event (for example, DeviceNet command from a controller or host)	Temperature, operating	-20...65 °C (-4...149 °F)	
<b>Alarms</b>				
Number	18 alarm and danger pairs Measurement value and rate of change value from each channel	Conformal Coating	All printed circuit boards are conformally coated in accordance with IPC-A-610C	
Operators	Greater than Less than Inside range Outside range	Temperature, operating	-20...65 °C (-4...149 °F)	
Hysteresis	User configurable in software	Temperature, surrounding air, max	65 °C (149 °F)	
<b>Relays</b>				
Number	Up to eight relays when interconnected to one or two XM-441 expansion relay modules or Eight virtual relays whose status can be used by remote control systems	Temperature, nonoperating	-40...85 °C (-40...185 °F)	
Failsafe	Normally energized (failsafe) or Normally de-energized (non-fail-safe)	IEC 60068-2-1 (Test Ab, Unpackaged Nonoperating Cold), IEC 60068-2-2 (Test Bd, Unpackaged Nonoperating Dry Heat), IEC 60068-2-14 (Test Nb, Operating Thermal Shock)		
Latching	Latching or Non-latching	IEC 60068-2-1 (Test Ab, Unpackaged Nonoperating Cold), IEC 60068-2-2 (Test Bd, Unpackaged Nonoperating Dry Heat), IEC 60068-2-14 (Test Na, Unpackaged Nonoperating Thermal Shock)		
Time delay	0...25.5 s, adjustable in 100 ms increments	Relative humidity	5...95% noncondensing	
Logic	Single or paired AND or OR logic applied to any alarm	Vibration	2 g @ 10...500 Hz	
Reset	Local reset switch on top of module Digital reset command via serial or DeviceNet interface	IEC 60068-2-6 (Test Fc, Operating)		
Activation on	Alarm status Normal Alert Danger Disarm Sensor Out of Range Module fault	Shock, operating	15 g	
		IEC 60068-2-27 (Test Ea, Unpackaged Shock)		
		Shock, nonoperating	20 g	
		IEC 60068-2-27 (Test Ea, Unpackaged Shock)		

Attribute	<b>XM-361 (1440-TUN06-00RE) XM-362 (1440-TTC06-00RE)</b>	Attribute	<b>XM-361 (1440-TUN06-00RE) XM-362 (1440-TTC06-00RE)</b>
Emissions CISPR 11 (IEC 61000-6-4)	Class A	CE	European Union 2004/108/EC EMC Directive, compliant with: <ul style="list-style-type: none"><li>• EN 61326-1; Meas./Control/Lab., Industrial Requirements</li><li>• EN 61000-6-2; Industrial Immunity</li><li>• EN 61000-6-4; Industrial Emissions</li><li>• EN 61131-2; Programmable Controllers (Clause 8, Zone A &amp; B)</li></ul>
ESD immunity IEC 61000-4-2	6 kV contact discharges 8 kV air discharges	C-Tick	Australian Radiocommunications Act, compliant with: <ul style="list-style-type: none"><li>• AS/NZS CISPR 11; Industrial Emissions</li></ul>
Radiated RF immunity IEC 61000-4-3	10V/m with 1 kHz sine-wave 80% AM from 80...2000 MHz 10V/m with 200 Hz 50% Pulse 100% AM at 900 MHz 10V/m with 200 Hz 50% Pulse 100% AM at 1890 MHz 3V/m with 1 kHz sine-wave 80% AM from 2000...2700 MHz	Ex	European Union 94/9/EC ATEX Directive, compliant with: <ul style="list-style-type: none"><li>• EN 60079-15; Potentially Explosive Atmospheres, Protection "n"</li><li>• EN 60079-11; Explosive Atmospheres, Protection "i"</li><li>• EN 60079-0; General Requirements</li><li>• II 3 G Ex nAC [ic] IIC T4X Gc</li></ul>
EFT/B immunity IEC 61000-4-4	±2 kV at 5 kHz on power ports ±1 kV at 5 kHz on shielded signal ports ±1 kV at 5 kHz on XMbus port	KC	Korean Registration of Broadcasting and Communications Equipment, compliant with: <ul style="list-style-type: none"><li>• Article 58-2 of Radio Waves Act, Clause 3</li></ul>
Surge transient immunity IEC 61000-4-5	±2 kV line-earth(CM) on shielded signal ports ±2 kV line-earth(CM) on XMbus port		
Conducted RF immunity IEC 61000-4-6	10V rms with 1 kHz sine-wave 80% AM from 150 kHz...80 MHz		
Enclosure type rating	None (open-style)		
Voltage and current ratings	XM-362 Supply: 24V DC, 0.3 A max, Class 2/SELV XM-361 Supply: 24V DC, 0.4 A max, Class 2/SELV		
Power dissipation	7.2 W max		
Isolation voltage	Not rated		
Wiring category <sup>(1)</sup>	2 - on shielded signal ports 3 - on Serial and power ports 2 - on XMbus ports		
Wire type	Signal connections: shielded Power connections: unshielded		
North American temp code	T4		
IEC temp code	T4		
<b>Physical</b>			
Terminal base	1440-TB-E		
Dimensions (H x W x D), approx	97 x 94 x 94 mm (3.8 x 3.7 x 3.7 in.)		
<b>Certification<sup>(2)</sup> (when product is marked)</b>	<b>Description</b>		
c-UL-us	UL Listed Industrial Control Equipment, certified for US and Canada. See UL File E234338.		
c-CSA-us	CSA Certified Process Control Equipment for Class I, Division 2 Group A,B,C,D Hazardous Locations, certified for US and Canada. See CSA File 150115.		